



LEDLight.com



130 Lumen output, .15 mA current @ 12.8 VDC. 2.69 Watt input consumption, 28 Watt equivalent output. 6000-6500 Kelvin Super White or 3000-3500 Kelvin Warm White. 10,000 hour life. 360 Degree viewing angle. Operating voltage 12V VDC. 2 inches in length. High tech heat sink to make the LED Light last longer. Designed for automotive, RV and marine uses along with many others. Now with Warm White and BA15D base configurations for RVs and boats. 1156 replaces BA15S T25 T-25 1073 1093 1129 1141 1159 1259 1295 1383 1459 1619 1651 1680 2056 3496 5007 5008 7008 7506 7806 7527 1156 1759 3497 1156-18W 67 89 97 1156 12821 P21W LOW 61 63 67 #67 69 71 81 89 97 98 303 623 1003 1155 1247 1251 3497 5007 5008 12821 P21W. 1157 replaces BAY15D 2057 2357 2397 7528 3496. BA15D replaces 90 1004 1076 1142.

Part#	34344
Part Description	12 SMT Tower S25 LED
Lamp Type	1156/1157 BA15D LED
Lamp Base	1156/1157 BA15D
Unit Wattage	2.88W
Voltage	12V
Frequency	50~60HZ
Operating Temperature Environment	lower than 60Deg
Operating Humidity	-20 to 60Deg
IP Class	5% to 95%
Ventilation	IP44
Weight	open air
Size	2.75kgs
Package Type	.65 in x 2.20in
Number/ Carton	LEDlight.com's card and blisters
Carton Size	500pcs/Ctn
Certificates	
Lense Type	CE & RoHS
Body Type	no lens
Work Environment	copper
Luminous Efficacy	indoor/outdoor
Lumen Maintenance	100%
LED Life	
Warranty	10000hrs
	see website for more information

Color	Beam Angle	Forward Lumen	Side Lumen	# of LEDs	# of chips per LED	LED Type	Kelvin	Wave Length	Unit Amps	LED Watts	Unit Watts	CRI
W	360	180L	0	12	3 chips	5050	6000-6500K		0.24A	0.24W	2.88W	75%
DW												
WW	360	145L	0	12	3 chips	5050	2700-3200K		0.24A	0.24W	2.88W	75%
R												
G												
B												
Y												
UV												
RGB												