

Product

42522 Standard Ultra Bright Five 1 Watt LED Light



Standard LED Light. 5 Watts. 350 Lumen. 300mA current. Consumes 5 Watts of power. Outputs 50 to 55 watt light equivalent. 85V-265V AC wide voltage range. Has 90% reflector efficiency. Dimpled clear lens helps diffuse light without reducing light output. Standard A19 Size packaging. Metal fin heat sink to help keep led light cool. Body temperature less than 70 degrees C. Is not compatible with a dimmer. Approximate size is 4.25in x 2.36in. IP Class: 50. Weight: 120g. CE, LVD, EMC listed. Lens Type: Honeycomb. Body Type: 6063 Aviation Aluminum. Luminous Efficacy: 75LM/W. Lumen maintenance: 380LM. Beam angle: 120/180 Degrees. Forward Lumen: 400Lm. Side Lumen: 350 Lm.

| Lens type | Clear/Dimpled | | | |
|-----------------------|----------------------|--|--|--|
| Body Type | Aluminum | | | |
| Work Environment | Indoor | | | |
| Efficacy | 75Lm/Watt | | | |
| Lumen Maintenance | 30% Decay @ 30,000Hr | | | |
| Led Life | Up To 50,000 Hr | | | |
| Operating Humidity | 30%~85% RH | | | |
| Operating Temp | 100°F@70°F Room temp | | | |
| Operating Environment | -4°F~104°F | | | |

| Lamp Type | Standard Light Bulb |
|-------------------|---------------------|
| Lamp Base | E27 |
| Unit Watts | 5.8 |
| Operating Voltage | 85-265V/AC |
| Frequency | 50Hz/60Hz |
| IP Class | 50 |
| Ventilation | Air |
| Size | 4.25in x 2.36in |
| | |

Toll Free: 1(877)283-5060

Local: 1(602)997-0366

Fax: 1(602)861-4088 Sales@ledlight.com

| UL | | ETL | | CE | | FCC | R | RoHs | |
|-------|--------|-------|-----------|-----------------------|----------|-------|-----------|------|--|
| No | | No | No Yes | | No | | , | Yes | |
| Color | Kelvin | Lumen | # of LEDs | # of Chips per LED | LED Type | Angle | LED Watts | CRI | |

| Color | Kelvin | Lumen | # of LEDs | # of Chips per LED | LED Type | Angle | LED Watts | CRI |
|---------|------------|-------|-----------|-----------------------|----------|-------|-----------|-----|
| 42522W | 5800-6300k | 400 | 5 | 1 | SMD | 120° | 1 | 80 |
| 42522SW | 4200-5200k | 400 | 5 | 1 | SMD | 120° | 1 | 80 |
| 42522WW | 2600-3000k | 400 | 5 | 1 | SMD | 120° | 1 | 80 |