

| | |
|----------------|--|
| Product | 45859 Standard Ultra Bright 7 SMT LED Light |
|----------------|--|



Available in white, warm white, red, green, blue and yellow. Uses 2.5W (45W estimated incandescent equivalent) 145 lumen output. Wide voltage range 85-260 VAC. Estimated average life up to 30,000 hours. Beam Width of 160 degrees. Frosted glass bulb. The warm white color is created by mixing red and yellow LEDs to create the perfect warm white color. The Standard Ultra Bright 7 SMT LED Light is commonly used for reading light, room lighting, accent lighting, vanity lighting and chandeliers. The 2.5W LED bulb replaces a 45W incandescent bulb and generates almost no heat. The LED light is made with a metal heat sink so it keeps the leds cooler which will make the LEDs last longer. Since the rated life of the bulb is estimated average life up to 30,000 hours, the bulb pays for itself by saving you both time and money. Length is 4.5" and diameter is 2". IP56. CE Listed. Fits standard E27 Base Edison screw base. This product is very well designed. The warm white is from 2700-3500 Kelvin and the white is from 5500-6500 Kelvin.

| | |
|------------------------------|----------------------|
| Lens type | Frosted |
| Body Type | Aluminum |
| Work Environment | Indoor |
| Efficacy | 58lm/Watt |
| Lumen Maintenance | 30% Decay @ 30,000Hr |
| Led Life | Up To 30,000 Hr |
| Operating Humidity | 25%~85% RH |
| Operating Temp | 100°F@70°F Room temp |
| Operating Environment | -4°F~104°F |

| | |
|--------------------------|---------------------|
| Lamp Type | Standard Light bulb |
| Lamp Base | E27 |
| Unit Watts | 2.5 |
| Operating Voltage | 85-260V/AC |
| Frequency | 50Hz/60Hz |
| IP Class | 56 |
| Ventilation | Air |
| Size | 4.35in x 2in |

| UL | ETL | CE | FCC | RoHs |
|----|-----|-----|-----|------|
| No | No | Yes | No | Yes |

| Color | Kelvin | Lumen | # of LEDs | # of Chips per LED | LED Type | Angle | LED Watts | CRI |
|---------|--------|-------|-----------|--------------------|----------|-------|-----------|-----|
| 45859W | 5000k | 145 | 7 | 1 | DIP | 360° | .5 | 85 |
| 45859WW | 3000k | 130 | 7 | 1 | DIP | 360° | .5 | 80 |
| 45859R | RED | 120 | 7 | 1 | DIP | 360° | .5 | 72 |
| 45859G | GREEN | 160 | 7 | 1 | DIP | 360° | .5 | 72 |
| 45859B | BLUE | 120 | 7 | 1 | DIP | 360° | .5 | 72 |
| 45859Y | YELLOW | 90 | 7 | 1 | DIP | 360° | .5 | 72 |