

Part#	48451
Part Description	S25 39 LED Light
Lamp Type	led car bulb
Lamp Base	1156/1157
Unit Wattage	2.61W
Voltage	14.5V
Frequency	H:180MA;L:60MA
Operating Temperature	(-)20Deg+80Deg
Environment Temperature	(-)20Deg+80Deg
Operating Humidity	5% to 95%
IP Class	IP 61 (1157)
Ventilation	open air
Weight	14.6g(1157) 15g (1156)
Size	H:44mm; D:25mm
Package Type	blister card
Number/ Carton	
Carton Size	38x28x22cm
Certificates	RoHS
Lense Type	
Body Type	
Work Environment	
Luminous Efficacy	
Lumen Maintenance	
LED Life	50000hours
Warranty	see website for more information



LEDLight.com



18 forward firing LEDs and 21 side firing LEDs. Forward firing 725 Lux, side firing 320 Lux. Durable, shock and vibration proof, instant On/Off. Monochromatic (pure) color, low heat generation, virtually unbreakable. Available in super white, red and yellow. 12 VDC. 1156 single contact is used for turn signals. 1157 dual contact is used for tail light/ brake light. 1156 replaces BA15S T25 T-25 1073 1093 1129 1141 1159 1259 1295 1383 1459 1619 1651 1680 2056 3496 5007 5008 7008 7506 7806 7527 1156 1759 3497 1156-18W 67 89 97 1156 12821 P21W LOW 61 63 67 #67 69 71 81 89 97 98 303 623 1003 1155 1247 1251 3497 5007 5008 12821 P21W. 1157 replaces BAY15D 2057 2357 2397 7528 3496.

Color	Beam Angle	Forward Lumen	Side Lumen	# of LEDs	# of chips per LED	LED Type	Kelvin	Wave Length	Unit Amps	LED Watts	Unit Watts	CRI
W	360 Deg	61 Lm	71 Lm	39 LED	1	18x4.6mm +21x3mm	6000-7000K		180mA	0.067W	2.61W	
DW												
WW												
R	360 Deg	12 Lm	11 Lm	39 LED	1	18x4.6mm +21x3mm		620-625nm	180mA	0.067W	2.61W	
G												
B												
Y	360 Deg	16 Lm	17 Lm	39 LED	1	18x4.6mm +21x3mm		590-595nm	180mA	0.067W	2.61W	
UV												
RGB												

LEDLight.com LLC
12215 East Chandler Heights Rd Chandler, AZ 85249
Toll Free 1(877)283-5060 Local 1(602)997-0366 Fax 1(602)861-4088