

57323	25W COMPACT UVC LAMP	UV-PRODUCT-SPEC.-0903 Revision:0 Page:1/2
-------	----------------------------	--

A General Data

1 Rated Voltage(60hz) 120-220V

2 Rated Current(60hz): 110mA

3 Lamp Wattage(Base up,60hz): 25W

45uW/cm²

B. Output(25°C,100hs,254nm)

UV Maintenance

80%

C Starting and Operation

1 Max. Starting time(198V,25): :

20S

300S

2 Time to reach 90% UV Output:

90% :

3 Temperture Range of the coldest point of the lamp to reach 90% UV Output: 40-50

90% :

4 Ambient Temperature Range(120-220V): Max:40 ,Min:10

5000H D Average Lifetime (220V,15-40 ,50% Failure)

Switching cycles(30sOn/30sOff)

>3000

E Safety

57323	25W COMPACT UVC LAMP	UV-PRODUCT-SPEC.-0903 Revision:0 Page:2/2
-------	----------------------------	--

Requirement(IEC61199.1993

Do protect your eyes and skin from the direct radiation.

F Dimensions

1 Overall Length (max) 215mm

Φ12 2 Tube

Diameter:

G Base

E27

H Glass Tube High Purity Quartz

Dry, and
Environment

Ventilation

I Storage Environment

Temperature of storage places:

Max:70 Min:-10

J

Lmax=215mm
X=136+/-2mm

